
flagit Documentation

Release unknown

TU Wien

Nov 10, 2022

Contents

1	Citation	3
2	Installation	5
3	Description	7
4	Contribute	9
4.1	Guidelines	9
5	Note	11
6	Run ISMN flag procedures	13
7	Contents	15
7.1	License	15
7.2	Contributors	15
7.3	Changelog	16
7.4	flagit	16
8	Indices and tables	17
	Python Module Index	19
	Index	21

ISMN quality control procedures for in situ soil moisture time series

CHAPTER 1

Citation

If you use the software in a publication then please cite:

- Dorigo, W.A. , Xaver, A. Vreugdenhil, M. Gruber, A., Hegyiova, A. Sanchis-Dufau, A.D., Zamojski, D. , Cordes, C., Wagner, W., and Drusch, M. (2013). Global Automated Quality Control of In situ Soil Moisture data from the International Soil Moisture Network. Vadose Zone Journal, 12, 3, doi:10.2136/vzj2012.0097
- <https://github.com/TUW-GEO/flagit>

CHAPTER 2

Installation

For installation we recommend [Miniconda](#). So please install it according to the official instructions. As soon as the conda command is available in your shell you can continue:

```
conda install -c conda-forge pandas scipy numpy
```

This following command will install the flagit pip package:

```
pip install flagit
```

To create a full development environment with conda, the environment.yml file in this repository can be used:

```
git clone git@github.com:TUW-GEO/flagit.git flagit
cd flagit
conda create -n flagit python=3.10 # or any supported python version
conda activate flagit
conda env update -f environment.yml -n flagit
python setup.py develop
```

After that you should be able to run:

```
python setup.py test
```

to run the test suite.

CHAPTER 3

Description

The International Soil Moisture Network (ISMN) quality control procedures are used to detect implausible and dubious measurements in hourly *situ* soil moisture time series. When downloading data at ISMN all variable-data are provided with additional tags in column “qflag”, which can be one of three main categories: C (exceeding plausible geophysical range), D (questionable/dubious) or G (good).

code	description	ancillary data required
C01	soil moisture < 0 m ³ /m ³	
C02	soil moisture > 0.60 m ³ /m ³	
C03	soil moisture > saturation point (based on HWSD)	HWSD sand, clay and organic content
D01	negative soil temperature (<i>in situ</i>)	<i>in situ</i> soil temperature
D02	negative air temperature (<i>in situ</i>)	<i>in situ</i> air temperature
D03	negative soil temperature (GLDAS)	GLDAS soil temperature
D04	rise in soil moisture without precipitation (<i>in situ</i>)	<i>in situ</i> precipitation
D05	rise in soil moisture without precipitation (GLDAS)	GLDAS precipitation
D06	spikes	
D07	negative breaks (drops)	
D08	positive breaks (jumps)	
D09	constant low values following negative break	
D10	saturated plateaus	
G	good	

At ISMN, ancillary data sets are used for flags C03, D01 - D05 (see table above). Since we do not provide ancillary data, we kindly ask users to either provide their own ancillary *in situ* and GLDAS data (including a soil moisture saturation value for flag C03) in the input (pandas.DataFrame), or accept the limitation of the quality control to flags without ancillary requirements.

We hope to update the functionality of this package to facilitate the inclusion of ancillary data.

For a detailed description of the quality control procedures see paper on [Global Automated quality control](#).

CHAPTER 4

Contribute

We would be happy if you would like to contribute. Please raise an issue explaining what is missing or if you find a bug. We will also gladly accept pull requests against our main branch for new features or bug fixes.

4.1 Guidelines

If you want to contribute please follow these steps:

- Fork the flagit repository to your account
- Clone the repository
- make a new feature branch from the flagit main branch
- Add your feature
- Please include tests for your contributions in one of the test directories. We use unittest so a simple function called `test_my_feature` is enough
- submit a pull request to our main branch

CHAPTER 5

Note

This project has been set up using PyScaffold 3.2.3. For details and usage information on PyScaffold see <https://pyscaffold.org/>.

CHAPTER 6

Run ISMN flag procedures

This example program shows how to initialize the Interface and run the flagging procedures.

As Input a pandas.DataFrame of the following format is required:

	soil_moisture	soil_temperature	air_temperature	precipitation	gldas_soil_temperature	gldas_precipitation
utc						
2017-01-27 00:00:00	5.0	-4.7	-13.6	0.0	-8.4	0.0
2017-01-27 01:00:00	4.9	-4.9	-13.4	0.0	-8.6	0.0
2017-01-27 02:00:00	4.9	-5.1	-14.0	0.0	-8.8	0.0
2017-01-27 03:00:00	4.9	-5.1	-13.2	0.0	-8.9	0.0
2017-01-27 04:00:00	4.9	-4.9	-11.2	0.0	-9.1	0.0
2017-01-27 05:00:00	4.9	-4.6	-10.1	0.0	-9.2	0.0
2017-01-27 06:00:00	5.0	-4.5	-8.9	0.0	-9.4	0.0

```
from flagit import flagit
import pandas as pd
```

```
# read from CSV file
file_path = '/path_to_dataframe/*.csv'
df = pd.read_csv(file_path, index_col='utc', parse_dates=True)
```

```
# initialize interface and run all flagging procedures
flag = flagit.Interface(df)
```

(continues on next page)

(continued from previous page)

```
result_df = flag.run(sat_point = 42.7)

# alternatively: choose only specific procedures by providing a list or string as
→name:
flag = flagit.Interface(df)
result_df = flag.run(name = ['D06', 'D07', 'D09'])
result_df = flag.run(name = 'C01')
```

```
# get flag-descriptions
flag = flagit.Interface(df)
flag.get_flag_description()
```

CHAPTER 7

Contents

7.1 License

The MIT License (MIT)

Copyright (c) 2020 TU Wien

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the “Software”), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED “AS IS”, WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

7.2 Contributors

- Daniel Aberer <daniel.aberer@geo.tuwien.ac.at>
- Angelika Xaver <angelika.xaver@geo.tuwien.ac.at>
- Wolfgang Preimesberger <wolfgang.preimesberger@geo.tuwien.ac.at>

7.3 Changelog

7.3.1 Version 0.1

- First public version of package

7.3.2 Version 0.2

- Adapt code for internal use
- Bugfix D06 rolling mean calculation
- Bugfix case of multiple precipitation sensors

7.4 flagit

7.4.1 flagit package

Submodules

flagit.flagit module

flagit.settings module

```
class flagit.settings.Variables
    Bases: object

    Class for flagging thresholds of soil moisture, accompanying ancillary observations and

    ancillary_p_min = 0.2
    ancillary_ta_lower = 0
    ancillary_ts_lower = 0

    hi_boundary(var)
        Upper threshold for quality control units: soil moisture : m3/m3 soil temperature, air temperture, surface
        temperature : degree Celsius precipitation, snow water equivalent, snow depth : mm soil suction : kPa
        var : string variable name (some examples are: soil_moisture, soil_temperature, snow_water_equivalent)

    low_boundary(var)
        Lower threshold for quality control units: soil moisture : m3/m3 soil temperature, air temperture, surface
        temperature : degree Celsius precipitation, snow water equivalent, snow depth : mm soil suction : kPa
        var : string variable name (some examples are: soil_moisture, soil_temperature, snow_water_equivalent)

    plateau_count = 0
```

Module contents

CHAPTER 8

Indices and tables

- genindex
- modindex
- search

Python Module Index

f

flagit, 16
flagit.settings, 16

Index

A

ancillary_p_min (*flagit.settings.Variables attribute*), 16
ancillary_ta_lower (*flagit.settings.Variables attribute*), 16
ancillary_ts_lower (*flagit.settings.Variables attribute*), 16

F

flagit (*module*), 16
flagit.settings (*module*), 16

H

hi_boundary () (*flagit.settings.Variables method*), 16

L

low_boundary () (*flagit.settings.Variables method*),
16

P

plateau_count (*flagit.settings.Variables attribute*),
16

V

Variables (*class in flagit.settings*), 16